

INVISIBLE



- ▶ Concealed outdoor unit
- ▶ R410A On-off
- ▶ Only 44cm height
- ▶ High pressure centrifugal fans
- ▶ Front air discharge
- ▶ Air inlet & discharge ducting option
- ▶ Easy transport, installation and maintenance

- Zone Control System (optional)
- Dual Control Operation
- I Feel
- Timer x4
- Indoor Hydrophilic Coating
- Sleep
- Motion Detector (optional)
- Autorestart
- Auto
- Wifi (optional)
- BMS**


ON-OFF DUCTED SYSTEMS



▶ INVISIBLE OUTDOOR UNIT



▶ WIND INDOOR UNIT



▶ WAVE INDOOR UNIT

		Units	Invisible Wave 36/3	Invisible Wind 48/3	Invisible Wind 60/3
Capacity	Cooling	kW	9.0	12.10	13.90
	Heating	kW	9.20	12.60	14.40
Power Input	Cooling	W	3.30	4.50	7.10
	Heating	W	3.20	4.40	5.00
Efficiency	Cooling/Energy Label	EER	2.70/D	2.70/D	2.70/D
	Heating/Energy Label	COP	2.88/D	2.88/D	2.88/D-
Operating Current	Cooling	A	8/3/3	9.8/4.8/4.8	10.8/5.8/5.8
	Heating	A	7.9/2.9/2.9	9.6/4.6/4.6	10.6/5.6/5.6
Humidity Removal		LIT/H	3.4	3.6	4
Input Voltage		V/Hz/Ph	400/50/3		
Fuse		A	3×16C		
INDOOR UNIT					
Piping		Inch	3/8"×5/8"	3/8"×3/4"	3/8"×3/4"
Dimensions (W×H×D)		mm	960×385×670	960×385×670	1,100×300×800
Airflow (high)		m ³ /h	2,380	3,332	3,332
Weight		Kg	50	47	47
CONCEALED OUTDOOR UNIT					
Dimensions (Width×Height×Depth)		mm	1,200×440×760	1,400×440×830	1,400×440×830
Airflow (high)		m ³ /h	3,621	4,683	5,780
Weight		Kg	132	140	150
Noise level (Pressure)		db(A)	62	62	64