

SWIFT INVERTER R32



► SWIFT INVERTER R32

- R32 DC Inverter
- Smart Wi-Fi (optional)
- Fast heating/cooling

- Precise temperature control
- Stepless fan speed
- -15°C super heating/cooling

- I Feel
- Timer
- Sleep
- Autorestart
- TURBO+** Turbo
- Auto Defrosting

- LED** LED Display
- Clock
- Self Diagnosis
- Anti-Mildew Design
- Filter Cleaning Reminder
- 0.5W Standby

INVERTER HIGH WALL UNITS



		Units	SWIFT INVERTER 9R	SWIFT INVERTER 12R	SWIFT INVERTER 18R	SWIFT INVERTER 24R
Function			Heat Pump	Heat Pump	Heat Pump	Heat Pump
Capacity	Cooling	BTU/h	8871	11942	17504	22007
	Heating	BTU/h	9554	12454	17981	22519
Capacity Range	Cooling	BTU/h	1365-11260	1877-13648	3412-22860	4777-23884
	Heating	BTU/h	1365-13989	2047-17504	3753-23202	5118-26955
SEER/SCOP		W/W	6.1/4.0	6.1/4.0	6.1/4.0	6.1/4.0
Energy Level		-	A++/A+	A++/A+	A++/A+	A++/A+
Power Supply		Ph, V, Hz	1ph, 220V-240V,50Hz	1ph, 220V-240V,50Hz	1ph, 220V-240V,50Hz	1ph, 220V-240V,50Hz
Power Input	Cooling	W	720	970	1500	1900
	Heating	W	735	960	1385	1780
Rated Current	Cooling	A	3.6	4.8	7.0	8.9
	Heating	A	3.4	4.4	6.3	8.4
INDOOR UNIT						
Refrigerant		-	R32	R32	R32	R32
Airflow Volume		m ³ /h	530/490/430/330	660/540/460/330	850/720/610/520	1090/930/670/560
Sound Pressure Level		db(A)(SH/H/M/L)	39/34/32/28	42/38/33/27	46/42/39/36	48/43/41/38
Outline Dimension W×H×D		mm	792×279×195	850×291×203	972×302×224	1081×327×248
Package Dimension W×H×D		mm	871×290×352	930×297×368	930×297×368	1158×352×413
Net Weight/Gross Weight		kg	9.5/12	10.5/13	14/17	16.5/20
OUTDOOR UNIT						
Sound Pressure Level		dB(A)	52	53	55	59
Piping Connection	Gas	mm	φ9.52	φ9.52	φ12	φ16
	Liquid	mm	φ6	φ6	φ6	φ6
Outline Dimension W×H×D		mm	830×540×325	830×540×325	890×598×372	960×700×396
Package Dimension W×H×D		mm	879×605×366	879×605×366	941×663×412	1011×763×455
Net Weight/Gross Weight		Kg	255	243	186	135